


XM-1000		Product Features
		◆ H.264 video compression
		◆ Support IE, Chrome, Firefox, Safari, Opera, etc.
		◆ High Definition 1280*720, clear image
		◆ P2P technology, plug and play, no any settings
		◆ Smart transmission technology: adaptive bandwidth, dynamic code rate adjustment, voice first, the jitter buffer
		◆ Support two-way audio, telecommunication level of signal processing, (echo cancellation, noise suppression, comfort noise, silence suppression)
		◆ Support Android /iOS system mobile devices, remote real-time monitoring(25 fps image transmission, 720P HD images)
		◆ Support multiple platforms, terminals, networks
		◆ Support remote firmware upgrade
		◆ Support multiple-users access ,multiple users management
		◆ Motion detection, real-time App push notifications
		◆ 2 pcs infrared LEDs, night vision distance: 10 meters, 24 hours day and night monitoring, IR-CUT switch
		◆ Support WIFI (IEEE802.11 b/g/n)
		◆ Support QR code login
		◆ Support micro SD card (max 32 GB) storage,Cloud box local recorde and cloud storage
Panda		◆ Support WPS function
Specifications		XM-1000
Image sensor	Image sensor	1/4 "color CMOS sensor
	Display resolution	1280 * 720 (720P)
	Lens	f: 2.1mm, F:2.0
	Viewing Angle (horizontal)	90 °
	Minimum illumination	0.5Lux
Audio	Input/output	Two-way audio(built-in microphone, external speaker)
	Audio compression	AAC(Advanced Audio Coding)
Video	Video compression	H.264
	Lighting frequency	50Hz, 60Hz
	Image frame rate	25fps
	Image resolution	1280*720, 640*360, 320*180, 160*90
	Image adjustment	Brightness, Contrast, Saturation, Sharpness
	White balance, BLC	Automatically
Internet	Night vision	2 infrared LEDs, IR distance: 10 meters
	Wireless networks	WiFi (IEEE802.11b/g/n), Built-in WiFi
	Ethernet	10/100Mbps RJ-45 interface
	Protocols	TCP/IP、UDP/IP、HTTP、SMTP、FTP、DHCP、DDNS、UPNP、RTSP、RTMP、MUTP
	IP address	Static IP address and dynamic IP address